## DocMan for each user
Posted by blpagno - 2009/12/08 14:41

---

Hi!

I'm using DocMan 1.4 in my sites. But I wanted to use a different folder to store the files for each user in my multisite. Is there a way to install the extension separatedly? Or any ideas how to separate eveyone's files?

Thanks in advance.

==========

## Re:DocMan for each user
Posted by edwin2win - 2009/12/08 19:19

---

Here it is two different methods:
1) In DocMan -> configuration menu, you can change the path for storinig files.
So you just have to go in its configuratoin.

2) If you deploy a slave site into a specific directory, you can also decide to create a physical "dmdocument " directory rather than to use the symbolic link (so use MKDIR).
You have to define that in a JMS template to create the slave site.

==========

## Re:DocMan for each user
Posted by blpagno - 2009/12/11 13:22

---

Thanks for the reply, Edwin.

It did work, to create physical "dmdocuments" using the MKDIR in the template. But... I still don't know how to configure each slave to use it's own folder.
The problem is that I have only one "docman.config.php", and that file is being used by all my sites. Is there a way to copy that file too so that I can configure each site individually, or a way to edit the file using php to generate the path "on the run"?

I really apreciate your help.

==========

## Re:DocMan for each user
Posted by blpagno - 2009/12/11 13:26

---

Ok... forget it... I just found out how it works.

Multisites creates other config files (docman.config..php) for each slave site.

Thanks for the help

==========

## Re:DocMan for each user

Posted by DaveC - 2010/07/31 03:06

---

Hi Edwin

To follow this up I have set the template to create the dmdocuments in the slave site and copy over the .htaccess.

The problem I am having is the configuration is still set for /var/www/html/dmdocuments instead of /var/www/html//dmdocuments

Would it be possible to have this configuration automated?

Thanks
Dave

==========

## Re:DocMan for each user

Posted by edwin2win - 2010/07/31 11:34

---

The path of the configuration is defined into the DocMan configuration menu.
So go in the slave site and modify it.

If you want to automate this path computation during a website creation, the only solution is to do add a specific script to modify the DocMan parameter present in its configuration that is stored on the disk. Such kind of script could be called during a website creation from the front-end but this require to enable the billable website functionality and to have quota available

==========