

## Initial Set up Questions

Posted by dx\_admin - 2011/10/02 23:40

---

Primary Question - Can someone point me to a tutorial or thread that shows the steps to map a slave (domain1.com) to a master (domain2.com)? I have seen the tutorials on using subdomains, but I am not finding a clear example when mapping a domain to the master. Make sense?

Secondary Questions - More just looking for advice on how someone with experience using JMS would set up my structure. Below is a brief sample of our structure:

This is a 3 tier structure. We will have a domain name as our primary. For example:

www.sportscentral.com

We then have 9 sites that come off of this domain. For example:

www.watersports.com, www.airsports.com, www.snowsports.com, etc

The final tier will be the use of subdomains off the tier two sites. For example:

www.rafting.watersports.com, www.surfing.watersports.com, etc

We are basically looking for any advice you 'experts' might have from setting up the relationships to how the databases are structured. Any advice would be greatly appreciated.

Thanks!

=====

## Re: Initial Set up Questions

Posted by edwin2win - 2011/10/03 12:07

---

1) If you are using cPanel, use the addOn domain to create the domain and provide a "document root" directory.

Follow our recommendation in tutorial video 0.b slide 21-24 that suggest how to naming the directories (document root) to ensure that you have a specific directory for each website.

When you have know the full path where is located your domain, you can give it in the "deployment folder" of JMS like illusatrated in video CP-04 (subdomains).

This is a cPanel (or other admin tool) configuration and you just have to provide in JMS the value that you have setup in your admin tool.

Apply the video 0.b slide 21-24 for the directory structure.

<http://www.jms2win.com/en/tutorial#jms12x-0b>

=====

## Re: Initial Set up Questions

Posted by dx\_admin - 2011/10/03 16:01

---

Thanks for the response! I tried that already and didn't have any luck - that is why I didn't think it was for a domain.

I will give it another try and pay attention to what I am doing so I can ask better questions if I get stuck again.

Thanks again.

=====

---

## Re: Initial Set up Questions

Posted by dx\_admin - 2011/10/04 01:02

---

I am not getting something here - not sure what step I am missing, but when I try to set up the domain using the 'Addons Domain' section of cPanel I am getting an error message that states - "Error from park wrapper: You cannot park your main domain!"

Below I am trying to take this step by step. Can you please fill in the blanks :huh:

For this example we will use www.master.com as the main site with the Joomla installation. Our goal is to get www.slave1.com set up as a secondary website. I followed the directions via the User Manual or at least I thought I did.

I have a VPS with HostGator and all my domains are up and working correctly.

Create an Addon Domain (this is the cpanel of www.slave1.com)

New Domain: slave1.com

Subdomain/FTP Username: anyone

Document Root: /public\_html/master (or master.com)

Password: password

I have tried several different iterations of this. I have watched the videos, but I am just not seeing this correctly. Any help would be appreciated.

=====

---

## Re: Initial Set up Questions

Posted by edwin2win - 2011/10/05 17:08

---

The cPanel addOn domain is used to add other domain than the "primary domain" assigned with you cPanel account.

So I suppose that you are trying to setup your primary domain and not an additional domain to your cPanel.

If you are using the "primary domain" as slave site, in this case, cPanel assign you "root" directory that is general something like /home/account/public\_html

So if you want in JMS create a slave site deployed in this directory, you just have to specify the full path in the "deployment folder" field.

If you follow our recommendation in the video 0.b slide 21 to 24, the value for a cPanel addon domain are

cPanel addon domain

domain = slave1.com

Subdomain/FTP = slave1

Document root = domains/slave1.com/public\_html

In JMS

Site ID = slave1

Domain = www.slave1.com, slave1.com

Deployment folder = /domains/slave1.com/public\_html

Replace by the home directory of you cPanel account (something like /home/XXXX where XXXX is you general your cPanel login)

=====

## Re: Initial Set up Questions

Posted by bonfiresalomon - 2012/06/04 23:24

---

Viveuk,

### COMPONENT:

You can now map your new domain (foobar.com,www.foobar.com) to the directory '/srv/www/lighttpd/j25\_base/multisites/Foo'.

### DOCUMENTATION:

When the new domain names are correctly routed to your Joomla directory ('/srv/www/lighttpd/j25\_base/'), the rest is performed by Jms Multi Sites.

You're spot on. Installation only 'fires' if the addon/subdomain is mapped to the Joomla master site's root, not the slave site's deployed directory. Mapping the addon/subdomain to the deploy directory results in the blank default index page (WSOD). Thanks for pointing out the discrepancy.

Edwin, would you please address this discrepancy between the documentation and the component specifically?

=====

## Re: Initial Set up Questions

Posted by edwin2win - 2012/06/05 17:03

---

The message that you receive is a generic message that tells you that when you assign the website (domain or subdomain) to the same directory as the master, this is also acceptable.

As you used the word "Addon Domain", I suppose that you are using a cPanel as administration tool. When using the cPanel "Addon Domain" or "subdomain" that allows you specifying a "document root", then you have to setup JMS "deploy folder" with the same path and vis versa.

In general, we recommend to start creating the Addon Domain or subdomain in cPanel to let cPanel create the "document root" directory.

After, when you define a JMS slave site and specify a wrong "deploy folder", you receive an error. When both the cPanel "document root" and "deploy folder" give the same path, the deployment is successful.

---

### Re: Initial Set up Questions

Posted by allyro - 2012/08/01 16:52

What happens in the following situation when working with one domain only, i.e. the main domain.

I've set up the master as a subdomain using the directory structure in the tutorials:

/domains/domain.com/subdomains/master/public\_html/

I now want to create a slave site in the main directory so I need to create the following:

/domains/domain.com/public\_html/

Because it's a main domain, cPanel won't allow me to handle it as an add-on. How do I then go about mapping www.domain.com to domains/domain.com/public\_html/ so that it's the same as the deploy folder?

---

### Re: Initial Set up Questions

Posted by edwin2win - 2012/08/01 22:04

When the "domain.com" is the primary domain of your cPanel then effectively, you can not change the location defined by cPanel.

The solution is to replace the /home/account/public\_html directory by a link to your

/home/account/domains/domain.com/public\_html

You can either do that manually with a SSH terminal command or declare a specific slave site inside JMS where you declare an "alias folder" that points to the /home/account/public\_html.

You will rename your /home/account/public\_html to /home/account/public\_html\_old before executing the rule to avoid receiving an error on that link.

The "alias folder" present in JMS creates a symbolic link on the "deploy folder".

---

### Re: Initial Set up Questions

Posted by allyro - 2012/08/21 13:28

Thanks :)