

## Auto generate multiple subdomains per slave site

Posted by dglite - 2009/05/21 14:11

---

Hi: I would like to share my experience with the community about using this component which I consider is great.

We needed to auto generate sub domains for each slave site...

On a domain we have this structure...

www.mydomain.com/my-dir/my-subdir1/index.php  
etc.

But we needed this...

www.my-subdir1.mydomain.com/index.php  
etc.

That way, you can have your own blog site like Wordpress, Blogspot, etc. for example...

myblog.wordpress.com

How to do this? Well we had been working on this for several days but in the end we figured it out how to do it, and is quite easy. Here the instructions, step by step:

1- You must enable Wildcard Subdomains on your server. This must be done by your Hosting Company. Ask them to enable that, so you can use this URL:

\*.mydomain.com

I was able to do it in cpanel after asking my company.

2- After that, you need to configure JMS as explained in their tutorial, but in when you generate the template, put this...

Valid domains or subdomains list... PUT: http://{site\_prefix}.{site\_url}

That way you will generate something like this...

mysubdomain.mydomain.com (like wordpress, blogspot, etc.)

If you need help just tell me.  
Greetings from Argentina.

ENJOY!!!

B)

=====

## Re:Auto generate multiple subdomains per slave site

Posted by edwin2win - 2009/05/21 15:18

---

Thank you for this guidance.

I think you should already find a similar answer in this forum that I have provided to this kind of request.

I would like to add some points:

- When you use `http://{site_prefix}.{site_url}`

becausefull that `{site_url}` may already contain "www" in front of the domain if your current master website is called with "www.domain.com" and not from "domain.com"

- In addition, when using the wildcard in the CPanel, this means that any sub-domain that is not defined in JMS will automatically display the master website.

You will not receive any error.

- When using wildcard, it is not possible to deploy the slave site into a specific directory as the CPanel will use the same documentroot directory.

When you have a full access on your server, perhaps you may have to consider using the "billable website" functionality that allow adding specific PHP script to create new entry in you CPanel. This could avoid the usage of the wildcard.

=====

## Re:Auto generate multiple subdomains per slave site

Posted by dglite - 2009/05/21 17:12

---

Hi: thanks for your great support. Regarding your topic, I need to know this...

1- how do I configure the component to have this...

`http://www.subdomain.domain.com/index.php`  
and

`http://subdomain.domain.com/index.php`

At the same time to target them to the same site?

Because you told me that `{site_url}` may already contain "www" in front of the domain if current master website is called with "www.domain.com" and not from "domain.com" (how do I change it?)

2- You tell me this...

"billable website" functionality that allow adding specific PHP script to create new entry in you CPanel...

But that means that all the subdomains will be automatically generated? I mean, I need the site to be like wordpress, and auto generate the subdomains so I do not have to do it myself in cpanel, is that possible? Could you explain how step by step?

3- By when would it be possible to install each slave site on a different database from the front end automatically once any user creates his website?

Thanks very much again, for your time and for this making great component!

B)

=====

## Re:Auto generate multiple subdomains per slave site

Posted by edwin2win - 2009/05/21 22:37

---

Q1) In JMS, you can give several domain in the definition.  
you just have to give several domain based on your sample  
`www.{site_prefix}.{site_url}`  
`{site_prefix}.{site_url}`

`{site_url}` contain the current URL and therefore the URL used to access your master website.  
If you want to be sure, you can hardcode your master domain name.  
put something like `{site_prefix}.domain.com`

Q2) All depend if you have a full access to your server and if you have the possibility to configure your CPanel dynamically.

You could develop a specific interface to your hosting server.

As this is specific to each hosting provider, JMS just provide the possibility to execute additional script.  
See user manual chapter 4.2 page 35 to 45 that describe all the possibilities

If you want that we help you in this development, this is possible with billable support.

We could work with you to develop such interface for your system.

Billable support can be ordered on

[http://www.jms2win.com/download?page=shop.product\\_details&flypage=flypage.tpl&product\\_id=35&category\\_id=1](http://www.jms2win.com/download?page=shop.product_details&flypage=flypage.tpl&product_id=35&category_id=1)

Q3) The current JMS 1.1.x does not allow to create slave site into another DB.

I am working on JMS 1.2.x that will allow replicate website into another DB.

It will have some constrain like having enough MySQL permission to create the DB and users.

I hope it will be released in june or july.

=====

## Re: Auto generate multiple subdomains per slave site

Posted by brayanlee - 2010/09/18 17:06

---

hello can you give the details on how you setup you JMS site template? I have activated the wildcard in my hostgator account for the domain name Im using glocalweb.co.cc. Its working with the wildcard but only in the backend or joomla admin. Frontend is totally blank, template is not displaying and also the content is not displaying.

this is my setup in the JMS site template: (pls tell me what is that im not doing right)

List of domain names:

`http://{site_url}/multisites/{site_alias}`

`http://{site_alias}.glocalweb.co.cc`

`http://www.{site_alias}.glocalweb.co.cc`

`http://{site_prefix}.{site_url}`

To site ID (\*): `{site_alias}`

New DB Prefix (\*): `{site_alias}{user_id}_`

Specific slave site folders

Master site folder: `/home/brayanle/public_html/glocalweb12546.co.cc`

Deployment folder: `{multisites}/{site_alias}`

Path to Media folder: `{multisites}/{site_alias}/images`

Path to Image folder: `{multisites}/{site_alias}/images/stories`

Templates (themes) folder: `{multisites}/{site_alias}/templates`

=====

## Re: Auto generate multiple subdomains per slave site

Posted by edwin2win - 2010/09/18 20:11

---

If you have a blank page in the front-end, this is the symptom of a PHP syntax error somewhere. Check the "error\_log" file that might provide you more detailed on the reason. Perhaps this will help you identify the extension that has a problem or cause the blank page.

If you have used a wildcard in the cPanel for a subdomain, that mean that the deploy directory is identical for all the subdomain.

As you could see it in tutorial video CP-05, try to have specific media, image and templates folders could be more difficult when sharing the same deployed directory for all the subdomain (because you use wildcard in cPanel).

In additiion your images and media setup are wrong as you provided a full path and it is required a relative path.

Here it is some suggestion to test

List of domain names:

`http://{site_alias}.glocalweb.co.cc`

`www.{site_alias}.glocalweb.co.cc`

To site ID (\*): `{site_alias}`

New DB Prefix (\*): `{site_alias}{user_id}_`

Specific slave site folders

Deployment folder: MUST BE THE SAME AS THE ONE ASSIGN FOR THE WILDCARD

Path to Media folder: Relative path - Problem all the subdomain will have same directory as you used a wildcard

Path to Image folder: Idem previous remark

Templates (themes) folder: `{deploy_dir}/templates`

=====

## Re: Auto generate multiple subdomains per slave site

Posted by brayanlee - 2010/09/19 09:46

---

---

Hello edwin2win thank you very much for the support i followed your instruction but I got a error screen.  
I attached the screen shots of the template and page after I created the site

<http://www.aviary.com/viewfull?fguid=81c54150-c3c3-11df-83eb-1231390ec091>  
<http://www.aviary.com/viewfull?fguid=dd222b62-c3cd-11df-83eb-1231390ec091>

=====

## Re: Auto generate multiple sudomains per slave site

Posted by edwin2win - 2010/09/19 12:39

---

The deploy directory is wrong.  
You have to provide a full path that correspond to the cPanel document root.  
You have forgotten the cPanel "home" directory.  
the path is /document root  
So this is ...../public\_html/.....

Probably you have to write the same value as the master webiste.  
If I read carrefully your path, you could use the keyword {root}

=====

## Re: Auto generate multiple sudomains per slave site

Posted by brayanlee - 2010/09/20 09:00

---

I change the deployment dir. to /home/brayanle/public\_html/glocalweb12546.co.cc/{site\_alias}

Additional Info:  
i pointed wildcard \*.glocvalweb.co.cc ----> public\_html/glocalweb12546.co.cc in cpanel

this domain is a addon domain glocalweb.co.cc  
thank you very much

=====

## Re: Auto generate multiple sudomains per slave site

Posted by edwin2win - 2010/09/20 12:57

---

So if the wildcard is pointed to public\_html/glocalweb12546.co.cc  
you can NOT put the {site\_alias} in the deploy folder as you mentioned it.

So deploy folder must be /home/brayanle/public\_html/glocalweb12546.co.cc

=====

## Re: Auto generate multiple sudomains per slave site

Posted by brayanlee - 2010/09/21 12:27

---

ok will try this again thank you very much

=====

## Re: Auto generate multiple sudomains per slave site

Posted by brayanlee - 2010/09/24 15:18

---

I tried what you said but its goes to the master site then i access the subsite

=====

## Re: Auto generate multiple sudomains per slave site

Posted by edwin2win - 2010/09/24 20:28

---

You have to cross-check the subdomain spelling in JMS Multisites.

If you have a wildcard, you must have the same directory for all the website or there is something else that I don't see for the moment.

=====