

## Remove /multisites from sub-directory slave's URL

Posted by meteu336 - 2009/06/01 10:08

---

I want to have slaves set as sub directories on my site (site.com/slave1, site.com/slave2, etc.) where site.com holds the main joomla installation. Right now, I get the custom Joomla 404 error for site.com/slave1, but the site comes up for site.com/multisites/slave1 even though both `http://{site_url}/{site_id}` and `http://{site_url}/multisites/{site_id}` are defined in the domain list.

Is there anyway for me to remove the /multisite from the URL?

=====

## Re:Remove /multisites from sub-directory slave's URL

Posted by edwin2win - 2009/06/01 10:39

---

The /multisites directory must exists on the disk because this is the place where JMS save all the website definition.

You can define only `http://{site_url}/{site_id}` and let the /multisites directory almost empty (not completely as JMS save its configuration in this directory).

What you can do is to ask deploying the slave site into the `{root}/{site_id}` directory that correspond to the domain `http://{site_url}/{site_id}`.

As JMS does not create the directory, you have to create the deploy directory before that you use it into JMS.

If you want completely deny all the access to the /multisites directory, you can add a ".htaccess" file with "deny from all".

In summary:

- Create a directory xxxx in you master website directory using FTP tool, SSH or other tool.

Go in JMS site manager

- Site ID = xxxx

- domain = `http://{site_url}/{site_id}`

- deploy directory = `{root}/{site_id}` : Remember that the directory must exists.

=====

## Re:Remove /multisites from sub-directory slave's URL

Posted by meteu336 - 2009/06/01 18:09

---

In the /site/multisites folder there are folders for all the slaves. Can I move those folders to the root, or do I have to leave them there in addition to creating the /site/slave1 folder?

=====

**Re:Remove /multisites from sub-directory slave's URL**

Posted by edwin2win - 2009/06/01 18:43

---

NO you can NOT move.

As I told you, JMS save its own configuration in those directories.

All you can do is to deny the access to thoses directories with a ".htaccess".

Apply the procedure described and you will see that you will have a very limited number of files into the /multisites/xxxx directories.

=====

**Re:Remove /multisites from sub-directory slave's URL**

Posted by meteu336 - 2009/06/01 22:06

---

When I use those steps, the site.com/slave1 now comes up, but with the initial Joomla installation guide instead of the slave site.

=====

**Re:Remove /multisites from sub-directory slave's URL**

Posted by edwin2win - 2009/06/02 00:30

---

Exact.

The sample that I have given to you use the tutorial step 9 procedure with another deploy directory.

If you want to replicate a website, you have to create a website template and select it.

See sample in the tutorial step 13 that show how to use website template fro the front-end. This procedure can also be used in the back-end.

=====